

## Technical Data Sheet

[www.soletex.com](http://www.soletex.com)

<b>Article- No</b>	KW 045 - PES-FLAG FABRIC	
<b>Application</b>	Banner / Flags / Beach Flags	
<b>Printable Ink</b>	Treatment applied for Sub Paper , Direct Sub., Latex, Uv-Curable	
<b>Material</b>	100 % Polyester	
<b>Standart Sizes</b>	App. 103 cm, 155 cm, 205 cm, 310 cm (40", 61", 80", 122") x 100mt. (109 yrd.)	
<b>Weight</b>	90 ( g/m2 )+- 5(gr) (3,1 oz)	
<b>Tensile Strength</b>	27/110 warp/weft (daN)	DIN EN ISO 13934-1
<b>Tear Resistance</b>	23/41 warp/weft (N)	DIN EN ISO 13937-4
<b>Finishing</b>	Digital Coating	
<b>Packaging</b>	3" paper core, wrapped with stretch film + put in a cardboard box	

Our product enables to have vivid colors and good printing quality with SUB., LATEX & UV inks.

(Test printing is suggested before the printing job.)



Ink Type



Sub Direct and Paper Transfer



UV Printable



Latex Printable



Fire Retardant



Fire Retardant



Fire Retardant



European Standard



Cutting



Cold Cut

\*Optional



Be Green ♻️

